

Club Car

ALWAYS DRIVEN



Ingersoll Rand is a global diversified firm providing products, services and solutions to enhance the quality and comfort of air in homes and buildings, transport and protect food and perishables, secure homes and commercial properties, and increase industrial productivity and efficiency. Driven by a 100-year-old tradition of technological innovation, we enable our customers to create progress and a positive impact in their world.


1.800.CLUBCAR • +1 706.863.3000

www.clubcar.com

www.ingersollrand.com

4/15 58648767

Please note vehicles contained throughout the brochure may be shown with additional accessories.





Always Driven.

For the golf course that aims to thrive in this hyper-competitive era, Carryall stands for the highest quality, most dependable and technologically advanced light-duty utility vehicles on the market. Add to that our commitment to service and support and the number one goal at Club Car® reveals itself: To be an indispensable partner in your operation's success.





The Legend. Reborn.



Electronic Fuel Injection:

A muscular, 14-horsepower rated engine that also reduces fuel consumption by up to 50%.



Rugged Bed Box:

VersAttach™ rail system organizes and secures cargo.



IQ Plus Electric Drive

System: Across the line upgrades integrate industry exclusive onboard global charger with cord reel, high-efficiency charging systems, improved amp hour tracking and charge confirmations.



Auto Styling and

Ergonomics: Inspired by the pickup you drive to work.

1,000 JOBS. ONLY ONE
CARRYALL

Redesigning the legendary Carryall is not a job you take on lightly. Or alone. Club Car® traveled the world to gauge what customers wanted. Their vision became our mission. Built on our 30-year legacy of performance and dependability, the all-new Carryall is more more powerful, versatile, efficient and comfortable, more of what makes Carryall the most valued utility vehicle in golf.

New EFI Engine:

More climb, less dime.



At the heart of the redesigned Carryall hums our new power plant, developed by Subaru and sporting a 14 horsepower rated engine. The overhead cam engine with electronic fuel injection (EFI) delivers a 30% power boost and still reduces fuel consumption by up to 50%.

Save on more than just fuel costs.

- Build quality, including case-hardened steel timing chain, lowers maintenance costs
- Runs cooler, quieter, with lower emissions
- Weathers all conditions; starts fast even on the coldest mornings
- Automatically adjusts for higher altitudes
- No carburetor or choke to master or maintain
- No oil filter to change; splash lubrication reduces maintenance
- Backed by the industry's best warranty

Every Carryall is dressed for golf.

Does any crew work like golf crews work? Not likely. Up before dawn, at it until nightfall chases you off the course, with a 1,000 different jobs in between. That's why we equip Carryalls for the unique demands of the golf operation. Your new vehicles arrive equipped and ready for the chores you encounter every day. From brush guard to trailer hitch, work with the best-dressed vehicles in golf.



Heavy-Duty Brush Guard:

Protection for those trips off the beaten path.



Durable Bed Box: Rust-proof, aircraft-grade aluminum with Rhino®-lined floor.



Green Cowl: The standard color designating golf utility vehicles.



Differential Guard: Protects the differential from damage in rugged terrain.



Turf-Friendly Tires: Bigger for more ground clearance, gentler on the turf.



Heavy-Duty Trailer Hitch: Built to handle heavy loads.

CARRYALL 500
TURF

Make molehills out of
mountains of work.



Carryall 550 Turf: The go-where-you-need-it utility vehicle.

With larger tires and higher ground clearance, Carryall 550 Turf can get in and out of places other vehicles avoid. And with its ample 500-lb. bed capacity, the 550 is the smart choice for medium-duty chores anywhere on the course where the terrain is challenging.



Carryall 500 Turf: Call in the muscle.

With 60% more bed capacity and 67% more towing capacity than the 550, Carryall 500 Turf is our flagship utility vehicle and the undisputed strong man in the 5-series. This economical yeoman is designed to take on big loads and demanding conditions to cut your biggest chores down to size.

CARRYALL 550
TURF

CARRYALL 7000
TURF

Fit-to-task and
fiscally fit



Built for the long haul.

Now available with the newly enhanced IQ Plus electric drive system and the all-new EFI gas engine, it's all about return on investment and nothing carries that responsibility like the Carryall 700 Turf. With 1,500 pounds of capacity and almost 6-feet of cargo bed, the 700 lives to handle your operation's most demanding jobs, all day long.

Versatility in a nimble package.

Carryall 300 Turf is a multi-tasking dynamo that can handle just about any light duty chore thrown its way. With either the new Subaru gas engine or our all-new electric system anchored by our new connected charger, E.R.I.C., driving its 900-pound capacity, the 300 is a sun-up-to-sundown laborer and hill-climbing whiz.

E.R.I.C.
EFFICIENT RELIABLE INTELLIGENT CONNECTED



The Carryall 300 Turf is the only utility vehicle equipped with E.R.I.C., Club's Car's all-new, advanced charging system. Efficient. Reliable. Intelligent. Connected. E.R.I.C. does it all. With cutting-edge features built into a smaller, lighter and infinitely smarter design, E.R.I.C. will have an immediate impact on your operation.

CARRYALL 300
TURF

CARRYALL 1500

Makes its mark by
not leaving any.



Carryall 1500 4-WD

When the job calls for more pull, Carryall 1500 4-WD answers the call.

- IntelliTrak® senses the terrain, delivers power to the front wheels when needed
- 25" all-terrain tires and 12.1" clearance handle demanding and tough conditions
- 4-wheel hydraulic disc brakes
- 25 mph maximum speed
- Roll Over Protective Structure (ROPS) certified to meet five different international standards

Carryall 1500 2-WD—heavy-duty capabilities that tread lightly on turf and improved surfaces. Two-wheel drive features include:

- Rear-wheel drive
- 23" front / 24" rear turf tires
- Handles up to 1,900 lbs. of payload
- 19 mph maximum speed

Haul more gear, more securely, using **VersAttach**.™



VersAttach, the all-new bed box rail system exclusively from Club Car®, expands your payload while securing whatever's on board. Sturdy channels engineered into the walls of the cargo box accept a variety of attachments—cleats, hooks and clamps—for storing, tying down and protecting tools and gear in transit.



Bed dividers help segregate and secure any size load.



Add/remove/relocate clamps and tie downs to fit your cargo.



Reinforced aluminum channels can handle almost any load.



A variety of equipment—cleats, hooks, clamps—are available to fit the tool and cargo.



Secure expensive power tools, protecting them from transit damage.



Attachment clamps are injection molded for solid fit and dependable performance.

ACCESSORIES

Equip your vehicles for maximum performance and comfort.

Every standard Carryall is ready to outwork, outperform and outlast everything else in its class. But when you want to tailor your vehicles to perform specialized tasks or adapt to the unique needs of your operation, Club Car® has the accessories and options to build out your Carryalls to perfection. Every accessory is designed and built specifically to work with Club Car vehicles.

4 x 2 accessories



Canopy Top



Heavy Duty Brush Guard



Stake-Side Kit



Receiver Hitch



Driving Range Protective Enclosure



Electric Bed Lift



ROPS Cab (Roll Over Protective Structure)



Soft Doors



Cab Outside Mirrors



LED Headlights



Accessory Switch Panel



Differential Guard



Hour Meter



Fuel Gauge/Hour Meter



Heavy Duty Batteries




Battery Capacity Indicator




Cargo Box Tool Box



Limited Slip Differential



Extra-Traction Turf Tires



Premium Tread 6-Ply Tires



5-Spoke Wheel Cover



All-Terrain Tires



Mud Tires



Cab Safety Strobe Light



Van Box



Swisher® Dump Cart

PHOTOS UNAVAILABLE:

- Universal Ball Picker Mount
- Flatbed Tool Box

4 x 4 accessories



Lighting Package (horn, turn signals, brake lights)



Rear Cargo Cage



Stake-Side Kit



2,500 lb. Warn Winch



54- or 62-Inch Plow Blade



40-Gallon Sprayer



Plastic Canopy Top



Electric Bed Lift



2-Inch Front Receiver Hitch



Pintle Hitch



Swisher® Trailmower



Cab Heater (Gas Only)



Underhood Storage (Gas Only)



Cargo Bed Toolbox



Nerf Bars



Swisher® Dump Cart

Not all accessories are available in all markets. Contact an authorized Club Car dealer for more information.

SPECIFICATIONS



CARRYALL 300 TURF



CARRYALL 500 TURF



CARRYALL 550 TURF



CARRYALL 700 TURF

	CARRYALL 300 TURF		CARRYALL 500 TURF	
	ELECTRIC	GASOLINE	ELECTRIC	GASOLINE
POWER SOURCE	48-volt DC	Subaru, 4-cycle	48-volt DC	Subaru, 4-cycle
ENGINE/MOTOR TYPE	48-volt DC	Subaru, 4-cycle	48-volt DC	Subaru, 4-cycle
CONTROLLER	500 Amp - Solid state	N/A	500 Amp - Solid state	N/A
DISPLACEMENT	N/A	404 cc	N/A	404 cc
CYLINDERS	N/A	Single	N/A	Single
VALVING	N/A	Overhead cam	N/A	Overhead cam
COOLING	N/A	Air cooled	N/A	Air cooled
HORSEPOWER (RATED)	3.3 hp (2.4 kW) rated, Peak 13 hp (9.6 kW)	14.0 hp (10.3 kW) rated @ 3,600 rpm per SAE J1940	3.7 hp (2.7 kW) rated, Peak 20 hp (14.9 kW)	14.0 hp (10.3 kW) rated @ 3,600 rpm per SAE J1940
MAX TORQUE	34.5 ft-lb (46.7 N-m) rated @ 1,980 rpm	19.91 ft lb (27.0 N-m) rated @ 2,400 rpm	71 ft-lb (96.2 N-m) rated @ 1,450 rpm	19.91 ft lb (27.0 N-m) rated @ 2,400 rpm
LUBRICATION	N/A	Splash lubrication	N/A	Splash lubrication
GOVERNOR	N/A	Ground speed	N/A	Ground speed
TRANSMISSION	Direct drive, double reduction helical gear	Continuously Variable Transmission (CVT)	Direct drive, double reduction helical gear	Continuously Variable Transmission (CVT)
FRONT/REAR DIFFERENTIAL	N/A	N/A	N/A	N/A
GEAR SELECTION	Forward/Neutral/Reverse	Forward/Neutral/Reverse	Forward/Neutral/Reverse	Forward/Neutral/Reverse
GEAR RATIO	12.32:1	11.47:1 forward; 15.63:1 reverse	12.32:1	11.47:1 forward; 15.63:1 reverse
IGNITION	N/A	Capacitive Discharge	N/A	Capacitive Discharge
BATTERY	Six 8-volt flooded lead acid	12-volt 500 CCA 105 min reserve	Eight 6-volt flooded lead acid	12-volt 500 CCA 105 min reserve
CHARGER	E.R.I.C. (650 W high frequency)	N/A	DeltaQ QuiQ (1 kW high frequency)	N/A
HEADLIGHTS	Two 37.5 watt halogen	Two 37.5 watt halogen	Two 37.5 watt halogen	Two 37.5 watt halogen
FUEL DELIVERY SYSTEM	N/A	Electronic Fuel Injection (EFI)	N/A	Electronic Fuel Injection (EFI)
FUEL CAPACITY	N/A	5.5 gal (20.8 L)	N/A	5.5 gal (20.8 L)
STEERING MECHANISM	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion
SUSPENSION (FRONT)	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks
SUSPENSION (REAR)	Semi-independent leaf spring with dual hydraulic shocks	Semi-independent leaf spring with dual hydraulic shocks	Semi-independent leaf spring with dual hydraulic shocks	Semi-independent leaf spring with dual hydraulic shocks
BRAKES	Rear mechanical drum	Rear mechanical drum	4-wheel mechanical drum	4-wheel mechanical drum
PARK BRAKE	Foot operated, Multi-lock	Foot operated, Multi-lock	Foot operated, Multi-lock	Foot operated, Multi-lock
BODY (FRONT & FINISH)	ArmorFlex® with automotive paint/clearcoat	ArmorFlex® with automotive paint/clearcoat	ArmorFlex® with automotive paint/clearcoat	ArmorFlex® with automotive paint/clearcoat
BODY (FRAME AND REAR)	Aluminum	Aluminum	Aluminum	Aluminum
TIRES (FRONT)	20 x 10-10, 6-ply	20 x 10-10, 6-ply	20 x 10-10, 6-ply	20 x 10-10, 6-ply
TIRES (REAR)	20 x 10-10, 6-ply	20 x 10-10, 6-ply	20 x 10-10, 6-ply	20 x 10-10, 6-ply
WHEELBASE	65.5 in (166.3 cm)	65.5 in (166.3 cm)	78.1 in (198.3 cm)	78.1 in (198.3 cm)
OVERALL HEIGHT	47.1 in (119.6 cm)	47.1 in (119.6 cm)	47.1 in (119.6 cm)	47.1 in (119.6 cm)
OVERALL LENGTH	110.1 in (279.6 cm)	110.1 in (279.6 cm)	118 in (299.7cm)	118 in (299.7cm)
BED L X W X H (CARGO BOX)	36.2 x 47.5 x 10.5 in (91.9 x 120.6 x 26.6 cm)	36.2 x 47.5 x 10.5 in (91.9 x 120.6 x 26.6 cm)	44.2 x 47.5 x 10.5 in (112.2 x 120.6 x 26.6 cm)	44.2 x 47.5 x 10.5 in (112.2 x 120.6 x 26.6 cm)
DIFFERENTIAL GROUND CLEARANCE	5.6 in (14.2 cm)	5.2 in (13.2 cm)	5.6 in (14.2 cm)	5.2 in (13.2 cm)
TRACK WIDTH (FRONT)	36.6 in (92.9 cm)	36.6 in (92.9 cm)	36.6 in (92.9 cm)	36.6 in (92.9 cm)
TRACK WIDTH (REAR)	39.5 in (100.3 cm)	39.5 in (100.3 cm)	39.5 in (100.3 cm)	39.5 in (100.3 cm)
MAX WIDTH (W/O MIRRORS)	50.3 in (127.7cm)	50.3 in (127.7cm)	50.3 in (127.7cm)	50.3 in (127.7cm)
CURB WEIGHT (W/ BATTERIES)	1,105 lb (501.2 kg)	817 lb (370. 5 kg)	1,393 lb (631.8 kg)	907 lb (411.4 kg)
TOTAL VEHICLE CAPACITY	800 lb (362.8 kg)	800 lb (362.8 kg)	1,200 lb (544.3 kg)	1,200 lb (544.3 kg)
BED LOAD CAPACITY	300 lb (136.0 kg)	300 lb (136.0 kg)	800 lb (362.8 kg)	800 lb (362.8 kg)
TOWING CAPACITY	800 lb (362.8 kg)	800 lb (362.8 kg)	1500 lb (680.3 kg)	1500 lb (680.3 kg)
COMBINED GROSS VEHICLE CAPACITY	800 lb (362.8 kg)	800 lb (362.8 kg)	1,500 lb (680.3 kg)	1,500 lb (680.3 kg)
SPEED	5-17 mph (8-27 kph)	15-17 mph (24-27 kph)	5-17 mph (8-27 kph)	15-17 mph (24-27 kph)
TURNING RADIUS	108.7 in (276.2 cm)	108.7 in (276.2 cm)	119 in (302.2 cm)	119 in (302.2 cm)
WARRANTY	4-year limited battery warranty; 3-year limited powertrain/frame; 2-year limited remaining vehicle	3-year/3,000 hr limited powertrain/frame; 2-year limited remaining vehicle	4-year limited battery warranty; 3-year limited powertrain/frame; 2-year limited remaining vehicle	3-year/3,000 hr limited powertrain/frame; 2-year limited remaining vehicle

	CARRYALL 550 TURF		CARRYALL 700 TURF	
	ELECTRIC	GASOLINE	ELECTRIC	GASOLINE
POWER SOURCE	48-volt DC	Subaru, 4-cycle	48-volt DC	Subaru, 4-cycle
ENGINE/MOTOR TYPE	48-volt DC	Subaru, 4-cycle	48-volt DC	Subaru, 4-cycle
CONTROLLER	500 Amp - Solid state	N/A	500 Amp - Solid state	N/A
DISPLACEMENT	N/A	404 cc	N/A	404 cc
CYLINDERS	N/A	Single	N/A	Single
VALVING	N/A	Overhead cam	N/A	Overhead cam
COOLING	N/A	Air cooled	N/A	Air cooled
HORSEPOWER (RATED)	3.7 hp (2.7 kW) rated, Peak 20 hp (14.9 kW)	14.0 hp (10.3 kW) rated @ 3,600 rpm per SAE J1940	3.7 hp (2.7 kW) rated, Peak 20 hp (14.9 kW)	14.0 hp (10.3 kW) rated @ 3,600 rpm per SAE J1940
MAX TORQUE	71 ft-lb (96.2 N-m) rated @ 1,450 rpm	19.91 ft lb (27.0 N-m) rated @ 2,400 rpm	71 ft-lb (96.2 N-m) rated @ 1,450 rpm	19.91 ft lb (27.0 N-m) rated @ 2,400 rpm
LUBRICATION	N/A	Splash lubrication	N/A	Splash lubrication
GOVERNOR	N/A	Ground speed	N/A	Ground speed
TRANSMISSION	Direct drive, double reduction helical gear	Continuously Variable Transmission (CVT)	Direct drive, double reduction helical gear	Continuously Variable Transmission (CVT)
FRONT/REAR DIFFERENTIAL	N/A	N/A	N/A	N/A
GEAR SELECTION	Forward/Neutral/Reverse	Forward/Neutral/Reverse	Forward/Neutral/Reverse	Forward/Neutral/Reverse
GEAR RATIO	12.32:1	11.47:1 forward; 15.63:1 reverse	12.32:1	11.47:1 forward; 15.63:1 reverse
IGNITION	N/A	Capacitive Discharge	N/A	Capacitive Discharge
BATTERY	Eight 6-volt flooded lead acid	12-volt 500 CCA 105 min reserve	Eight 6-volt flooded lead acid	12-volt 500 CCA 105 min reserve
CHARGER	DeltaQ QuiQ (1 kW high frequency)	N/A	DeltaQ QuiQ (1 kW high frequency)	N/A
HEADLIGHTS	Two 37.5 watt halogen	Two 37.5 watt halogen	Two 37.5 watt halogen	Two 37.5 watt halogen
FUEL DELIVERY SYSTEM	N/A	Electronic Fuel Injection (EFI)	N/A	Electronic Fuel Injection (EFI)
FUEL CAPACITY	N/A	5.5 gal (20.8 L)	N/A	5.5 gal (20.8 L)
STEERING MECHANISM	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion
SUSPENSION (FRONT)	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks
SUSPENSION (REAR)	Semi-independent leaf spring with dual hydraulic shocks	Semi-independent leaf spring with dual hydraulic shocks	Semi-independent leaf spring with dual hydraulic shocks	Semi-independent leaf spring with dual hydraulic shocks
BRAKES	4-wheel mechanical drum	4-wheel mechanical drum	4-wheel mechanical drum	4-wheel mechanical drum
PARK BRAKE	Foot operated, Multi-lock	Foot operated, Multi-lock	Foot operated, Multi-lock	Foot operated, Multi-lock
BODY (FRONT & FINISH)	ArmorFlex® with automotive paint/clearcoat	ArmorFlex® with automotive paint/clearcoat	ArmorFlex® with automotive paint/clearcoat	ArmorFlex® with automotive paint/clearcoat
BODY (FRAME AND REAR)	Aluminum	Aluminum	Aluminum	Aluminum
TIRES (FRONT)	22 x 10-10, 4-ply Turf tread; 22 x 10-10, 6-ply heavy-duty all-terrain	22 x 10-10, 4-ply Turf tread; 22 x 10-10, 6-ply heavy-duty all-terrain	20 x 10-10, 6-ply	20 x 10-10, 6-ply
TIRES (REAR)	22 x 10-10, 4-ply Turf tread; 22 x 10-10, 6-ply heavy-duty all-terrain	22 x 10-10, 4-ply Turf tread; 22 x 10-10, 6-ply heavy-duty all-terrain	20 x 10-10, 6-ply	20 x 10-10, 6-ply
WHEELBASE	78.1 in (198.3 cm)	78.1 in (198.3 cm)	99.1 in (251.7 cm)	99.1 in (251.7 cm)
OVERALL HEIGHT	51.2 in (130.0 cm)	51.2 in (130.0 cm)	47.1 in (119.6 cm)	47.1 in (119.6 cm)
OVERALL LENGTH	118 in (299.7cm)	118 in (299.7cm)	137.5 in (349.3 cm)	137.5 in (349.3 cm)
BED L X W X H (CARGO BOX)	44.2 x 47.5 x 10.5 in (112.2 x 120.6 x 26.6 cm)	44.2 x 47.5 x 10.5 in (112.2 x 120.6 x 26.6 cm)	65.5 x 47.5 x 10.5 in (166.3 x 120.6 x 26.6cm)	65.5 x 47.5 x 10.5 in (166.3 x 120.6 x 26.6cm)
DIFFERENTIAL GROUND CLEARANCE	6 in (15.2 cm)	6 in (15.2 cm)	5.6 in (14.2 cm)	5.2 in (13.2 cm)
TRACK WIDTH (FRONT)	36.6 in (92.9 cm)	36.6 in (92.9 cm)	36.6 in (92.9 cm)	36.6 in (92.9 cm)
TRACK WIDTH (REAR)	39.5 in (100.3 cm)	39.5 in (100.3 cm)	39.5 in (100.3 cm)	39.5 in (100.3 cm)
MAX WIDTH (W/O MIRRORS)	50.3 in (127.7cm)	50.3 in (127.7cm)	50.3 in (127.7cm)	50.3 in (127.7cm)
CURB WEIGHT (W/ BATTERIES)	1,402 lb (635.9 kg)	942 (427.2 kg)	1,475 lb (669 kg)	993 lb (450.4 kg)
TOTAL VEHICLE CAPACITY	900 lb (408.2 kg)	900 lb (408.2 kg)	1,200 lb (544 kg)	1,200 lb (544 kg)
BED LOAD CAPACITY	500 lb (226.7 kg)	500 lb (226.7 kg)	1,000 lb (453.5 kg)	1,000 lb (453.5 kg)
TOWING CAPACITY	900 lb (408.2 kg)	900 lb (408.2 kg)	1,500 lb (680.3 kg)	1,500 lb (680.3 kg)
COMBINED GROSS VEHICLE CAPACITY	900 lb (408.2 kg)	900 lb (408.2 kg)	1,500 lb (680.3 kg)	1,500 lb (680.3 kg)
SPEED	5-17 mph (8-27 kph)	15-17 mph (24-27 kph)	5-17 mph (8-27 kph)	15-17 mph (24-27 kph)
TURNING RADIUS	126.5 in (321.3 cm)	126.5 in (321.3 cm)	162.8 in (413.4 cm)	162.8 in (413.4 cm)
WARRANTY	4-year limited battery warranty; 3-year limited powertrain/frame; 2-year limited remaining vehicle	3-year/3,000 hr limited powertrain/frame; 2-year limited remaining vehicle	4-year limited battery warranty; 3-year limited powertrain/frame; 2-year limited remaining vehicle	3-year/3,000 hr limited powertrain/frame; 2-year limited remaining vehicle

SPECIFICATIONS



CARRYALL 1500 4x2



CARRYALL 1500 4x4



CARRYALL 1500 4x4 INTELLITACH



CARRYALL 1700 4x4

	GASOLINE	GASOLINE	DIESEL
POWER SOURCE	GASOLINE	GASOLINE	DIESEL
ENGINE	Kawasaki 4-cycle, industrial grade	Kawasaki 4-cycle, industrial grade	Kubota D722, industrial grade
CONTROLLER	N/A	N/A	N/A
DISPLACEMENT	675 cc	675 cc	719 cc
CYLINDERS	Twin-cylinder	Twin-cylinder	3-cylinder
VALVING	OHV	OHV	OHV
COOLING	Air cooled	Air cooled	Liquid cooled
HORSEPOWER (RATED)	20.1 hp (15.0 kW) rated @ 3,400 rpm per SAE J1349	20.1 hp (15.0 kW) rated @ 3,400 rpm per SAE J1349	20.0 hp (15.0 kW) rated @ 3,600 rpm per SAE J1995
MAX TORQUE	36.5 ft/lb (49.5 Nm)	36.5 ft/lb (49.5 Nm)	33 ft/lb (45 Nm)
LUBRICATION	Full-pressure, spin-on oil filter	Full-pressure, spin-on oil filter	Full-pressure, spin-on oil filter
GOVERNOR	Automatic ground speed sensing	Automatic ground speed sensing	Automatic ground speed sensing
TRANSMISSION	Wide ratio CVT; 3.7:1 low, 0.59:1 high	Wide ratio CVT; 3.7:1 low, 0.59:1 high	Wide ratio CVT; 3.7:1 low, 0.59:1 high
FRONT/REAR DIFFERENTIAL	Automatic locking rear differential	IntelliTrak™ Automatic 4-wheel Drive	IntelliTrak™ Automatic 4-wheel Drive
GEAR SELECTION	Forward/Neutral/Reverse	Forward/Neutral/Reverse	Forward/Neutral/Reverse
GEAR RATIO	5.39:1 forward, 7.79:1 reverse, 3.3:1 differential	5.39:1 forward, 7.79:1 reverse, 3.3:1 differential	5.39:1 forward, 7.79:1 reverse, 3.3:1 differential
IGNITION	Transistorized magneto	Transistorized magneto	Compression
BATTERY	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve
CHARGER	N/A	N/A	N/A
HEADLIGHTS	Headlights standard	Headlights standard	Headlights standard
FUEL DELIVERY SYSTEM	Carburetor	Carburetor	Mechanical injection
FUEL CAPACITY	6.5 gal (24.6 L)	6.5 gal (24.6 L)	6.5 gal (24.6 L)
STEERING MECHANISM	Rack and pinion with Tilt Steering	Rack and pinion with Tilt Steering	Rack and pinion with Tilt Steering
SUSPENSION (FRONT)	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks
SUSPENSION (REAR)	Semi-independent 4-link solid axle	Semi-independent 4-link solid axle	Semi-independent 4-link solid axle
BRAKES	Twin piston front, single piston rear hydraulic disk	Twin piston front, single piston rear hydraulic disk	Twin piston front, single piston rear hydraulic disk
PARK BRAKE	Mechanical Disk	Mechanical Disk	Mechanical Disk
BODY (FRONT & FINISH)	GE Geloy high-impact, scratch-resistant, injection molded color, automotive finish	GE Geloy high-impact, scratch-resistant, injection molded color, automotive finish	GE Geloy high-impact, scratch-resistant, injection molded color, automotive finish
BODY (FRAME AND REAR)	Tubular aluminum	Tubular aluminum	Tubular aluminum
TIRES (FRONT)	4-ply Turf; 23 x 10.5 x 12	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply
TIRES (REAR)	4-ply Turf; 24 x 10.5 x 12	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply
WHEELBASE	88.7 in (225.3 cm)	88.7 in (225.3 cm)	88.7 in (225.3 cm)
OVERALL HEIGHT	52.6 in (133.5 cm)	78.6 in (199.6 cm)	78.6 in (199.6 cm)
OVERALL LENGTH	124.6 in (316.5 cm)	124.6 in (316.5 cm)	124.6 in (316.5 cm)
BED L X W X H (CARGO BOX)	48.8 x 49.8 x 10.9 in (124 x 126.5 x 27.7 cm)	48.8 x 49.8 x 10.9 in (124 x 126.5 x 27.7 cm)	48.8 x 49.8 x 10.9 in (124 x 126.5 x 27.7 cm)
DIFFERENTIAL GROUND CLEARANCE	7.3 in (18.5 cm)	8.2 in (20.8 cm)	8.2 in (20.8 cm)
TRACK WIDTH (FRONT)	48.8 in (124 cm)	48.8 in (124 cm)	48.8 in (124 cm)
TRACK WIDTH (REAR)	48.8 in (124 cm)	48.8 in (124 cm)	48.8 in (124 cm)
MAX WIDTH (W/O MIRRORS)	58.5 in (148.5 cm)	58.5 in (148.5 cm)	58.5 in (148.5 cm)
CURB WEIGHT (NO BATTERIES)	1,410 lb (639.57 kg)	1,430 lbs (648.6 kg)	1,550 lbs (703.1 kg)
TOTAL VEHICLE CAPACITY	1,450 lb (658 kg)/1,900 lb (862 kg)*	1,200 lb (544 kg)/1,450 lb (658 kg)**	1,200 lb (544 kg)/1,450 lb (658 kg)**
BED LOAD CAPACITY	1,050 lb (476.3 kg)/1,900 lb (862 kg)*	800 lb (363.2 kg)/1,050 lb (658 kg)**	800 lb (363.2 kg)/1,050 lb (658 kg)**
TOWING CAPACITY	1,450 lb (658 kg)/1,900 lb (862 kg)*	1,200 lb (544 kg)/1,450 lb (658 kg)**	1,200 lb (544 kg)/1,450 lb (658 kg)**
COMBINED VEHICLE CAPACITY	1,450 lb (658 kg)/1,900 lb (862 kg)*	1,200 lb (544 kg)/1,450 lb (658 kg)**	1,200 lb (544 kg)/1,450 lb (658 kg)**
SPEED	19 mph (30.6 km/h)	25 mph (40.2 km/h)	25 mph (40.2 km/h)
TURNING RADIUS	152 in (386.1 cm)	152 in (386.1 cm)	152 in (386.1 cm)
WARRANTY	2-year/2,000 hour limited	2-year/2,000 hour limited	2-year/2,000 hour limited

*3/4-ton option; ** High-capacity option

	DIESEL	GASOLINE	DIESEL
POWER SOURCE	DIESEL	GASOLINE	DIESEL
ENGINE	Kubota D722, industrial grade	Kawasaki 4-cycle, industrial grade	Kubota D722, industrial grade
CONTROLLER	N/A	N/A	N/A
DISPLACEMENT	719 cc	675 cc	719 cc
CYLINDERS	3-cylinder	Twin-cylinder	3-cylinder
VALVING	OHV	OHV	OHV
COOLING	Liquid cooled	Air cooled	Liquid cooled
HORSEPOWER (RATED)	20.0 hp (15.0 kW) rated @ 3,600 rpm per SAE J1995	20.1 hp (15.0 kW) rated @ 3,400 rpm per SAE J1349	20.0 hp (15.0 kW) rated @ 3,600 rpm per SAE J1995
MAX TORQUE	33 ft/lb (45 Nm)	36.5 ft/lb (49.5 Nm)	33 ft/lb (45 Nm)
LUBRICATION	Full-pressure, spin-on oil filter	Full-pressure, spin-on oil filter	Full-pressure, spin-on oil filter
GOVERNOR	Automatic ground speed sensing	Automatic ground speed sensing	Automatic ground speed sensing
TRANSMISSION	Wide ratio CVT; 3.7:1 low, 0.59:1 high	Wide ratio CVT; 3.7:1 low, 0.59:1 high	Wide ratio CVT; 3.7:1 low, 0.59:1 high
FRONT/REAR DIFFERENTIAL	IntelliTrak™ Automatic 4-wheel Drive	IntelliTrak™ Automatic 4-wheel Drive	IntelliTrak™ Automatic 4-wheel Drive
GEAR SELECTION	Forward/Neutral/Reverse	Forward/Neutral/Reverse	Forward/Neutral/Reverse
GEAR RATIO	5.39:1 forward, 7.79:1 reverse, 3.3:1 differential	5.39:1 forward, 7.79:1 reverse, 3.3:1 differential	5.39:1 forward, 7.79:1 reverse, 3.3:1 differential
IGNITION	Compression	Transistorized magneto	Compression
BATTERY	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve
CHARGER	N/A	N/A	N/A
HEADLIGHTS	Headlights standard	Headlights standard	Headlights standard
FUEL DELIVERY SYSTEM	Mechanical injection	Carburetor	Mechanical injection
FUEL CAPACITY	6.5 gal (24.6 L)	6.5 gal (24.6 L)	6.5 gal (24.6 L)
STEERING MECHANISM	Rack and pinion with Tilt Steering	Rack and pinion with Tilt Steering	Rack and pinion with Tilt Steering
SUSPENSION (FRONT)	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks
SUSPENSION (REAR)	Semi-independent 4-link solid axle	Semi-independent 4-link solid axle	Semi-independent 4-link solid axle
BRAKES	Twin piston front, single piston rear hydraulic disk	Twin piston front, single piston rear hydraulic disk	Twin piston front, single piston rear hydraulic disk
PARK BRAKE	Mechanical Disk	Mechanical Disk	Mechanical Disk
BODY (FRONT & FINISH)	GE Geloy high-impact, scratch-resistant, injection molded color, automotive finish	GE Geloy high-impact, scratch-resistant, injection molded color, automotive finish	GE Geloy high-impact, scratch-resistant, injection molded color, automotive finish
BODY (FRAME AND REAR)	Tubular aluminum	Tubular aluminum	Tubular aluminum
TIRES (FRONT)	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply
TIRES (REAR)	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply
WHEELBASE	88.7 in (225.3 cm)	114 in (225.3 cm)	114 in (225.3 cm)
OVERALL HEIGHT	78.6 in (199.6 cm)	78.6 in (199.6 cm)	78.6 in (199.6 cm)
OVERALL LENGTH	148.6 in (377.4 cm)	157.6 in (400.3 cm)	157.6 in (400.3 cm)
BED L X W X H (CARGO BOX)	48.8 x 49.8 x 10.9 in (124 x 126.5 x 27.7 cm)	48.8 x 49.8 x 10.9 in (124 x 126.5 x 27.7 cm)	48.8 x 49.8 x 10.9 in (124 x 126.5 x 27.7 cm)
DIFFERENTIAL GROUND CLEARANCE	8.2 in (20.8 cm)	8.2 in (20.8 cm)	8.2 in (20.8 cm)
TRACK WIDTH (FRONT)	48.8 in (124 cm)	48.8 in (124 cm)	48.8 in (124 cm)
TRACK WIDTH (REAR)	48.8 in (124 cm)	48.8 in (124 cm)	48.8 in (124 cm)
MAX WIDTH (W/O MIRRORS)	58.5 in (148.5 cm)	58.5 in (148.5 cm)	58.5 in (148.5 cm)
CURB WEIGHT (NO BATTERIES)	1,710 lb (775.64 kg)	1,630 lb (739.36 kg)	1,750 lb (793.8 kg)
TOTAL VEHICLE CAPACITY	1,700 lb (771.1 kg)	1,600 lb (725.8 kg)	1,600 lb (725.8 kg)
BED LOAD CAPACITY	800 lb (363.2 kg)	800 lb (363.2 kg)	800 lb (363.2 kg)
TOWING CAPACITY	1,700 lb (771.1 kg)	1,600 lb (725.8 kg)	1,600 lb (725.8 kg)
COMBINED VEHICLE CAPACITY	1,700 lb (771.1 kg)	1,600 lb (725.8 kg)	1,600 lb (725.8 kg)
SPEED	25 mph (40.2 km/h)	25 mph (40.2 km/h)	25 mph (40.2 km/h)
TURNING RADIUS	160 in (406.4 cm)	206.5 in (524.5 cm)	206.5 in (524.5 cm)
WARRANTY	2-year/2,000 hour limited	2-year/2,000 hour limited	2-year/2,000 hour limited

*There are no warranties, express or implied, contained herein. See Limited Warranty found in the owner's manual or write to Club Car, LLC. Vehicle specifications are accurate for each model at the time of publication. The company reserves the right to make design changes without obligation to make these changes on units previously sold. These vehicles are designed and manufactured for off-road use only. They do not conform to Federal Motor Vehicle Safety Standards for automobiles or to FMVSS 500 for low-speed vehicles and are not equipped for operation on public streets, roads or highways.